Application No.: 10/519,572

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in

the application:

Listing of Claims:

1. - 33. (Canceled)

34. (Currently amended) Sanitary component (1) having a jet regulating device

(4) in an interior of a mounting housing, the jet regulating device (4) comprising: at

least one mounted element mountable in the mounting housing, that has ridges (11)

oriented transverse to a direction of flow, between which passageways (12) are

defined, wherein the ridges (11) of the at least one mounted element (5a, 5b, 5c, 5d,

5e) are arranged in the form of a grid or mesh, which cross at junction points (10)

located in a single plane.

35. (Currently Amended) Component according to claim 34, wherein the jet

regulating device (4) on an inflow side is downstream from a jet separating device.

for the separation of the inflowing fluid flow into a multitude of individual jets and

the at [[the]] least one mounted element (5a, 5c) of the jet regulating device (4) is

arranged relative to the jet separating device such that the individual jets impinge

upon junction points (10) of the at least one mounted element (5a, 5c).

- 2 -

Application No.: 10/519,572

36. (Original) Component according to claim 35, wherein the jet separating

device is shaped as a perforated plate (2).

37. (Previously Presented) Component according to claim 34, wherein at least

two neighboring of the at least one mounted elements (5a, 5b, 5c, 5d, 5e) are

provided with ridges (11) arranged in the form of a grid or mesh.

38. (Previously Presented) Component according to claim 37, wherein the ridges

(11) and the junction points (10) of the at least two neighboring mounted elements

(5a, 5b) align with one another.

39. (Previously Presented) Component according to claim 34, wherein at least

two of the at least one mounted elements (5a, 5b) are structurally identical.

40 (Currently Amended) Component according to claim 34, wherein the

passageways (12) of one of the of the at least one mounted elements (5a, 5c) are

downstream upstream of the junction points (10) of a neighboring mounted

elements (5b, 5e) in the direction of the flow.

- 3 -

Applicant: Hermann Grether Application No.: 10/519,572

41. (Previously Presented) Component according to claim 34, wherein at least

one inflow side or one outflow side mounted element is arranged in a plane that is

oriented transverse to the direction of flow.

42. (Currently Amended) Component according to claim 34, wherein a mounted

element (5a, 5b) [[on]] at an inflow- or outflow side is arranged in the form of a grid

and comprises two groups of parallel grid ridges (11) that cross one another.

43. (Currently Amended) Component according to claim 34, wherein one of the

at least one mounted element (5c, 5e) [[on]] at an inflow- or outflow side has a group

of radial ridges (11') that cross at the junction points (10) with a group of rotary

ridges (11") that are concentric and in the form of a ring.

44. (Currently Amended) Component according to claim 34, wherein one of the

at least one mounted element (5d) [[on]] at an inflow- or outflow side has ridges (11)

that cross in a star-shape or in the form of a mesh.

45. (Previously Presented) Component according to claim 34, wherein the ridges

(11) of at least one of the at least one mounted element (5) are arranged in a plane

oriented transverse to the direction of flow

- 4 -

Application No.: 10/519,572

46. (Previously Presented) Component according to claim 34, wherein the at

least one mounted element (5) is shaped in the form of discs.

47. (Previously Presented) Component according to claim 34, wherein the jet

regulating device (4) is upstream of a flow regulator (14), the flow regulator (14)

comprising passage openings (15) whose opening width (15) is smaller than a height

thereof in the direction of flow.

48. (Original) Component according to claim 47, wherein the flow regulator (14)

is attached at the discharge end of the mounting housing (6).

49. (Original) Component according to claim 47, wherein the flow regulator (14)

is connected in one piece with the mounting housing (6) or can be directly mounted

in the mounting housing (6) as a separate mounted element.

50 (Previously Presented) Component according to claim 47, wherein the flow

regulator (14) comprises through passage openings (15) that are rectangular, in the

form of segments of a circle or in the form of a honeycomb.

- 5 -

Applicant: Hermann Grether Application No.: 10/519,572

51. (Currently Amended) Component according to claim 36, wherein the

mounting housing is divided into at least two housing parts (7, 8), such that the at

least two housing parts (7, 8) are detachably connectable with one another, and

such that one of the at least two housing parts (7) [[on the]]  $\underline{at\ an}$  inflow side is fixed

and nondetachably connected with the perforated plate (2).

52. (Previously Presented) Component according to claim 51, wherein the jet

separating device (2) is integral with one of the at least two housing parts (7).

53. (Previously Presented) Component according to claim 34, wherein the

mounting housing (6) has two housing parts (7, 8) that are detachable and that can

be combined with one another and oriented in a parting plane transverse to the

direction of flow.

54. (Currently amended) Component according to claim 34, wherein the

mounting housing (6) comprises at least two housing parts (7, 8) of the mounting

housing (6) that are detachably connected with one another.

55. (Currently amended) Component according to claim [[41]] 53, wherein a

housing part (8) [[on the]] at an outflow side is arranged in the form of a sleeve and

the at least one mounted element (5) of the jet regulating device (4) is mountable

- 6 -

Application No.: 10/519.572

therein.

56. (Currently amended) Component according to claim 55, wherein the at least

one mounted element (5) of the jet regulating device whose-discharge-side is

insertable into a corresponding housing part (8) [[tol] and abuts a plug stop (9) or a

support.

57. (Previously Presented) Component according to claim 51, wherein the

mounting housing comprises at least two housing parts (7, 8) that can be combined

with one another and in which at least two jet regulating devices can be mounted.

58 (Previously Presented) Component according to claim 47, wherein the jet

regulating device or the flow regulator includes at least one metal filter.

59. (Previously Presented) Component according to claim 34, wherein the jet

regulating device of the component (1) is constructed in a modular manner and

multiple mounted elements (5a, 5b, 5c, 5e) are attached to one another.

60. (Previously Presented) Component according to claim 34, wherein the at

least one mounted element (5), is at least two mounted elements, which are

arranged spaced from one another at a distance.

- 7 -

Application No.: 10/519,572

61. (Currently amended) Component according to claim 55, wherein the housing

part (8) [[on]] at the outflow side possesses at least one soft or water-repellent water

surface at least in a water discharge opening area.

62. (Currently amended) Component according to claim 55, wherein the housing

part (8) [[onl] at the outflow side is manufactured out of an elastic material at least

in a water discharge opening area.

63. (Currently amended) Component according to claim 55, wherein the housing

part (8) [[onl] at the outflow side is manufactured substantially out of an elastic

material or a material with a soft or water-repellent surface.

64 - 65(Cancelled)

66 (Currently Amended) Component according to claim 55, wherein the housing

part (8) [[on]] at the outflow side in a water discharge opening area comprises at

least one constriction (23) or equivalent narrowing of its flow-through cross section.

- 8 -

Applicant: Hermann Grether Application No.: 10/519,572

67. (Previously Presented) Component according to claim 51, wherein a housing part (8) towards an outflow side is connectable to a neighboring housing part (7) towards an inflow side via a snap-on connection.